



IR	4"	420	55	OO	G	I	BP	PG	4AC	PP	XZ5																																															
<table border="1"> <thead> <tr> <th>Sector</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Irrigation</td> <td>IR</td> </tr> </tbody> </table>		Sector	Code	Irrigation	IR																																																					
Sector	Code																																																									
Irrigation	IR																																																									
<table border="1"> <thead> <tr> <th>Size</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>DN25</td><td>1"</td></tr> <tr><td>DN40</td><td>1.5"</td></tr> <tr><td>DN50</td><td>2"</td></tr> <tr><td>DN65</td><td>2.5"</td></tr> <tr><td>DN80</td><td>3"</td></tr> <tr><td>DN100</td><td>4"</td></tr> <tr><td>DN150</td><td>6"</td></tr> <tr><td>DN200</td><td>8"</td></tr> <tr><td>DN250</td><td>10"</td></tr> </tbody> </table>		Size	Code	DN25	1"	DN40	1.5"	DN50	2"	DN65	2.5"	DN80	3"	DN100	4"	DN150	6"	DN200	8"	DN250	10"																																					
Size	Code																																																									
DN25	1"																																																									
DN40	1.5"																																																									
DN50	2"																																																									
DN65	2.5"																																																									
DN80	3"																																																									
DN100	4"																																																									
DN150	6"																																																									
DN200	8"																																																									
DN250	10"																																																									
		<table border="1"> <thead> <tr> <th>Primary Feature</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>Basic Valve</td><td>405</td></tr> <tr><td>Solenoid Controlled Valve</td><td>410</td></tr> <tr><td>Pressure Reducing Valve</td><td>420</td></tr> <tr><td>Pressure Reducing & Sustaining Valve</td><td>423</td></tr> <tr><td>Pressure Sustaining Valve</td><td>430</td></tr> <tr><td>Surge Anticipating Valve</td><td>435</td></tr> <tr><td>Differential Pressure Sustaining Valve</td><td>436</td></tr> <tr><td>Quick Pressure Relief Valve</td><td>43Q</td></tr> <tr><td>Level Control Valve</td><td>450</td></tr> <tr><td>Level Control & Pressure Sustaining Valve</td><td>453</td></tr> <tr><td>Level & Flow Control Valve</td><td>457</td></tr> <tr><td>Flow Control Valve</td><td>470</td></tr> <tr><td>Flow Control & Pressure Reducing Valve</td><td>472</td></tr> <tr><td>Flow Control & Pressure Sustaining Valve</td><td>473</td></tr> <tr><td>Flow Control & Pressure Reducing & Sustaining Valve</td><td>475</td></tr> </tbody> </table>		Primary Feature	Code	Basic Valve	405	Solenoid Controlled Valve	410	Pressure Reducing Valve	420	Pressure Reducing & Sustaining Valve	423	Pressure Sustaining Valve	430	Surge Anticipating Valve	435	Differential Pressure Sustaining Valve	436	Quick Pressure Relief Valve	43Q	Level Control Valve	450	Level Control & Pressure Sustaining Valve	453	Level & Flow Control Valve	457	Flow Control Valve	470	Flow Control & Pressure Reducing Valve	472	Flow Control & Pressure Sustaining Valve	473	Flow Control & Pressure Reducing & Sustaining Valve	475																							
Primary Feature	Code																																																									
Basic Valve	405																																																									
Solenoid Controlled Valve	410																																																									
Pressure Reducing Valve	420																																																									
Pressure Reducing & Sustaining Valve	423																																																									
Pressure Sustaining Valve	430																																																									
Surge Anticipating Valve	435																																																									
Differential Pressure Sustaining Valve	436																																																									
Quick Pressure Relief Valve	43Q																																																									
Level Control Valve	450																																																									
Level Control & Pressure Sustaining Valve	453																																																									
Level & Flow Control Valve	457																																																									
Flow Control Valve	470																																																									
Flow Control & Pressure Reducing Valve	472																																																									
Flow Control & Pressure Sustaining Valve	473																																																									
Flow Control & Pressure Reducing & Sustaining Valve	475																																																									
		<p>Other primary features available on request.</p>																																																								
		<table border="1"> <thead> <tr> <th>Secondary Feature - Multiple Options Permitted</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>No Additional Features</td><td>00</td></tr> <tr><td>Closing and Opening Speed Control</td><td>03</td></tr> <tr><td>Hydraulic Override</td><td>03</td></tr> <tr><td>Electric Control</td><td>18</td></tr> <tr><td>Solenoid Controller & Check Feature</td><td>25</td></tr> <tr><td>Two-Stage Opening</td><td>30</td></tr> <tr><td>Two-Stage Opening & Electric Control</td><td>35</td></tr> <tr><td>Relief Override</td><td>3Q</td></tr> <tr><td>Electrically Selected Multi-Level Setting</td><td>45</td></tr> <tr><td>Downstream Over Pressure Guard</td><td>48</td></tr> <tr><td>Closing Surge Prevention</td><td>49</td></tr> <tr><td>Hydraulic Relay</td><td>50</td></tr> <tr><td>Normally Closed with PC Hydraulic Relay</td><td>54X</td></tr> <tr><td>Solenoid Controlled</td><td>55</td></tr> <tr><td>Electric Override</td><td>59</td></tr> <tr><td>Modulating Horizontal Float</td><td>60</td></tr> <tr><td>Bi-Level Electric Float</td><td>65</td></tr> <tr><td>Bi-Level Vertical Float</td><td>66</td></tr> </tbody> </table>		Secondary Feature - Multiple Options Permitted	Code	No Additional Features	00	Closing and Opening Speed Control	03	Hydraulic Override	03	Electric Control	18	Solenoid Controller & Check Feature	25	Two-Stage Opening	30	Two-Stage Opening & Electric Control	35	Relief Override	3Q	Electrically Selected Multi-Level Setting	45	Downstream Over Pressure Guard	48	Closing Surge Prevention	49	Hydraulic Relay	50	Normally Closed with PC Hydraulic Relay	54X	Solenoid Controlled	55	Electric Override	59	Modulating Horizontal Float	60	Bi-Level Electric Float	65	Bi-Level Vertical Float	66																	
Secondary Feature - Multiple Options Permitted	Code																																																									
No Additional Features	00																																																									
Closing and Opening Speed Control	03																																																									
Hydraulic Override	03																																																									
Electric Control	18																																																									
Solenoid Controller & Check Feature	25																																																									
Two-Stage Opening	30																																																									
Two-Stage Opening & Electric Control	35																																																									
Relief Override	3Q																																																									
Electrically Selected Multi-Level Setting	45																																																									
Downstream Over Pressure Guard	48																																																									
Closing Surge Prevention	49																																																									
Hydraulic Relay	50																																																									
Normally Closed with PC Hydraulic Relay	54X																																																									
Solenoid Controlled	55																																																									
Electric Override	59																																																									
Modulating Horizontal Float	60																																																									
Bi-Level Electric Float	65																																																									
Bi-Level Vertical Float	66																																																									
		<p>Other additional features available on request.</p>																																																								
		<table border="1"> <thead> <tr> <th>Pattern</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>Globe</td><td>G</td></tr> <tr><td>Angle - Available for: 2", 2.5", 3" and 4"</td><td>A</td></tr> </tbody> </table>		Pattern	Code	Globe	G	Angle - Available for: 2", 2.5", 3" and 4"	A																																																	
Pattern	Code																																																									
Globe	G																																																									
Angle - Available for: 2", 2.5", 3" and 4"	A																																																									
		<table border="1"> <thead> <tr> <th>Construction Materials</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>Cast Iron (up to 8")</td><td>I</td></tr> <tr><td>Ductile Iron</td><td>C</td></tr> </tbody> </table>		Construction Materials	Code	Cast Iron (up to 8")	I	Ductile Iron	C																																																	
Construction Materials	Code																																																									
Cast Iron (up to 8")	I																																																									
Ductile Iron	C																																																									
		<p>Other materials available on request.</p>																																																								
		<table border="1"> <thead> <tr> <th>End Connection</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>BSP-T Female Threaded - Available for: 1" - 3")</td><td>BP</td></tr> <tr><td>BSPT-D - Flanged - Available from 3" and larger</td><td>BD</td></tr> <tr><td>BSPT-E - Flanged - Available only for 4"</td><td>BE</td></tr> <tr><td>ANSI C 606-81, Steel Pipe - Grooved (Globe - 2", 3", 4", 6" & 8")</td><td>VI</td></tr> </tbody> </table>		End Connection	Code	BSP-T Female Threaded - Available for: 1" - 3")	BP	BSPT-D - Flanged - Available from 3" and larger	BD	BSPT-E - Flanged - Available only for 4"	BE	ANSI C 606-81, Steel Pipe - Grooved (Globe - 2", 3", 4", 6" & 8")	VI																																													
End Connection	Code																																																									
BSP-T Female Threaded - Available for: 1" - 3")	BP																																																									
BSPT-D - Flanged - Available from 3" and larger	BD																																																									
BSPT-E - Flanged - Available only for 4"	BE																																																									
ANSI C 606-81, Steel Pipe - Grooved (Globe - 2", 3", 4", 6" & 8")	VI																																																									
		<p>Other end connections available on request.</p>																																																								
								<table border="1"> <thead> <tr> <th>Coating</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>Polyester Green - RAL6017</td><td>PG</td></tr> </tbody> </table>		Coating	Code	Polyester Green - RAL6017	PG																																													
Coating	Code																																																									
Polyester Green - RAL6017	PG																																																									
								<table border="1"> <thead> <tr> <th>Voltage</th> <th>Main Valve Position (When Solenoid De-Energized)</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>24VAC, with Diode</td><td>Normally Closed</td><td>4AC</td></tr> <tr><td>24VAC, with Diode</td><td>Normally Open</td><td>4A0</td></tr> <tr><td>24VAC</td><td>Last Position</td><td>4AP</td></tr> <tr><td>24VAC</td><td>Normally Closed</td><td>4RC</td></tr> <tr><td>24VAC</td><td>Normally Open</td><td>4R0</td></tr> <tr><td>24VDC</td><td>Normally Closed</td><td>4DC</td></tr> <tr><td>24VDC</td><td>Normally Open</td><td>4D0</td></tr> <tr><td>24VDC</td><td>Last Position</td><td>4DP</td></tr> <tr><td>12VDC</td><td>Normally Closed</td><td>1DC</td></tr> <tr><td>12VDC</td><td>Normally Open</td><td>1D0</td></tr> <tr><td>12VDC</td><td>Last Position</td><td>1DP</td></tr> <tr><td>12VDC</td><td>Latch Solenoid - S985 (3 Leads)</td><td>1DS</td></tr> <tr><td>12VDC</td><td>Latch Solenoid - S982 (2 Leads)</td><td>2DS</td></tr> <tr><td>9VDC</td><td>Latch Solenoid</td><td>9DS</td></tr> </tbody> </table>		Voltage	Main Valve Position (When Solenoid De-Energized)	Code	24VAC, with Diode	Normally Closed	4AC	24VAC, with Diode	Normally Open	4A0	24VAC	Last Position	4AP	24VAC	Normally Closed	4RC	24VAC	Normally Open	4R0	24VDC	Normally Closed	4DC	24VDC	Normally Open	4D0	24VDC	Last Position	4DP	12VDC	Normally Closed	1DC	12VDC	Normally Open	1D0	12VDC	Last Position	1DP	12VDC	Latch Solenoid - S985 (3 Leads)	1DS	12VDC	Latch Solenoid - S982 (2 Leads)	2DS	9VDC	Latch Solenoid	9DS				
Voltage	Main Valve Position (When Solenoid De-Energized)	Code																																																								
24VAC, with Diode	Normally Closed	4AC																																																								
24VAC, with Diode	Normally Open	4A0																																																								
24VAC	Last Position	4AP																																																								
24VAC	Normally Closed	4RC																																																								
24VAC	Normally Open	4R0																																																								
24VDC	Normally Closed	4DC																																																								
24VDC	Normally Open	4D0																																																								
24VDC	Last Position	4DP																																																								
12VDC	Normally Closed	1DC																																																								
12VDC	Normally Open	1D0																																																								
12VDC	Last Position	1DP																																																								
12VDC	Latch Solenoid - S985 (3 Leads)	1DS																																																								
12VDC	Latch Solenoid - S982 (2 Leads)	2DS																																																								
9VDC	Latch Solenoid	9DS																																																								
								<p>Other electrical ratings available on request.</p>																																																		
								<table border="1"> <thead> <tr> <th>Tubings & Fittings</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>Plastic Tubing & Fittings (Standard)</td><td>PP</td></tr> <tr><td>Plastic Reinforced Tubing & Brass Fittings</td><td>PB</td></tr> <tr><td>Copper Tubing & Brass Fittings</td><td>CB</td></tr> </tbody> </table>		Tubings & Fittings	Code	Plastic Tubing & Fittings (Standard)	PP	Plastic Reinforced Tubing & Brass Fittings	PB	Copper Tubing & Brass Fittings	CB																																									
Tubings & Fittings	Code																																																									
Plastic Tubing & Fittings (Standard)	PP																																																									
Plastic Reinforced Tubing & Brass Fittings	PB																																																									
Copper Tubing & Brass Fittings	CB																																																									
								<table border="1"> <thead> <tr> <th>Additional Attributes - Unlimited Selection</th> <th>Code</th> </tr> </thead> <tbody> <tr><td>3-Way Control Loop</td><td>X</td></tr> <tr><td>Plastic Control Accessories</td><td>K</td></tr> <tr><td>Metal Control Accessories</td><td>R</td></tr> <tr><td>External Control Pressure</td><td>e</td></tr> <tr><td>EPDM Elastomer Seals & Diaphragm</td><td>E1</td></tr> <tr><td>Large Control Filter</td><td>F</td></tr> <tr><td>Valve Position Indicator *</td><td>I</td></tr> <tr><td>Flow Stem *</td><td>M</td></tr> <tr><td>Electric Limit Switch *</td><td>S</td></tr> <tr><td>Orifice Assembly</td><td>U</td></tr> <tr><td>Paddle Flow Control Pilot</td><td>V</td></tr> <tr><td>Manual Selector</td><td>Z</td></tr> <tr><td>Low Preset Pressure (below 2 bar)</td><td>2</td></tr> <tr><td>High Upstream Pressure (above 10 bar)</td><td>3</td></tr> <tr><td>Plastic Pressure Test Point</td><td>5</td></tr> <tr><td>Pressure Gauge</td><td>6</td></tr> <tr><td>Double - Pressure Gauge</td><td>66</td></tr> <tr><td>Schreader Valve</td><td>SCH</td></tr> <tr><td>Double - Schreader Valve</td><td>SCH SCH</td></tr> </tbody> </table>		Additional Attributes - Unlimited Selection	Code	3-Way Control Loop	X	Plastic Control Accessories	K	Metal Control Accessories	R	External Control Pressure	e	EPDM Elastomer Seals & Diaphragm	E1	Large Control Filter	F	Valve Position Indicator *	I	Flow Stem *	M	Electric Limit Switch *	S	Orifice Assembly	U	Paddle Flow Control Pilot	V	Manual Selector	Z	Low Preset Pressure (below 2 bar)	2	High Upstream Pressure (above 10 bar)	3	Plastic Pressure Test Point	5	Pressure Gauge	6	Double - Pressure Gauge	66	Schreader Valve	SCH	Double - Schreader Valve	SCH SCH									
Additional Attributes - Unlimited Selection	Code																																																									
3-Way Control Loop	X																																																									
Plastic Control Accessories	K																																																									
Metal Control Accessories	R																																																									
External Control Pressure	e																																																									
EPDM Elastomer Seals & Diaphragm	E1																																																									
Large Control Filter	F																																																									
Valve Position Indicator *	I																																																									
Flow Stem *	M																																																									
Electric Limit Switch *	S																																																									
Orifice Assembly	U																																																									
Paddle Flow Control Pilot	V																																																									
Manual Selector	Z																																																									
Low Preset Pressure (below 2 bar)	2																																																									
High Upstream Pressure (above 10 bar)	3																																																									
Plastic Pressure Test Point	5																																																									
Pressure Gauge	6																																																									
Double - Pressure Gauge	66																																																									
Schreader Valve	SCH																																																									
Double - Schreader Valve	SCH SCH																																																									
								<p>* Standard Irrigation Cover & Diaphragm are not suitable for Attributes: I, M, S.</p>																																																		
								<p>Other additional attributes are optional. Please consult with Deeco for further information.</p>																																																		