

# Sensus PulseRF Radio Transponder



## Application

The Sensus PulseRF provides a solution to integrate meters with pulse output into the SensusRF Radio Network. The solution is mainly used with C&I water meters, but also other meters with pulse output as thermal energy, gas or electricity meters can be implemented.

It is designed to transmit meter data in intervals or readout further information with mobile readout devices or a fixed radio network transceiver.

The Sensus PulseRF creates data from incoming pulses and transmits them to an external data management system (for example meter index, alarms or additional information as Fixed Date Reading or Data Logger)

In addition to transmitting the meter index, the Sensus PulseRF transponder allows numerous other smart functions which provide added customer value.

## Special Features

Transmission of consumption values

Data Logging (by steps of 1 min to 24h)

Active alarm status (cable cut or removal, leakage, broken pipe, reverse flow, low battery)

Pulse Input

Flow Direction Input

Units for Energy and Volume

## Technical Specifications

### General

Dimensions max.: 45 x 115 x 40 mm  
 Weight: 230 g  
 Casing: ABS  
 Colour: Grey  
 Electronics & battery sealed  
 Cable length: 2.5 m  
 Max. cable length: 15 m

### Power supply

Lithium battery  
 Battery life: typically 15+ years depending on usage profile

### Radio specification

433 MHz at 10mW  
 868 MHz at 25mW

### Radio protocol

SensusRF radio protocol bi-directional  
 FlexNet protocol (TFX) bi-directional  
 wMBus OMS unidirectional

### Environmental

Operation: min -20 °C / max +60 °C  
 Storage: min -20 °C / max +70 °C  
 Protection rating: IP68

### Mounting bracket

The transponder can be fixed on a wall with a mounting bracket which is part of the consignment

### Recycling

Has to be recycled according to national rules for electronic devices with lithium batteries.

### Applied Standards

EN 62479; EN 60950-1;  
 Radio frequency: EN 300 220-1/-2  
 EMC: EN 301 489-1/-3  
 RoHS, WEEE

### Accessories

To connect Sensus PulseRF to a meter with pulse unit we recommend:

Jointing sleeve IP 68, order no. 18 17 84  
 Connector IP68 for two cables up to 5 wires



## Pulse Interface

Meters with a pulse output, as open collector or reed switch, can be connected. The Sensus PulseRF has one 4 wire input enabling the following functions

- Pulse input (+) (white)
- Cable cut (green)\*
- Direction (yellow)\*
- Ground (-) (brown)

Min. pulse length	32 ms
Min. pulse pause	60 ms
Max. pulse frequency	10 Hz
Detection for closed	(0....0.7) V
Detection for open	(2.0....2.5) V
Max. cable capacity	10 nF
Max. bouncing time (Reed)	2,5 ms
Internal pull up resistance	10 kOhm
Internal pull up voltage	2.5 V

### Configuration interface

The transponder can be configured using SensusRF radio with SIRT and configuration software.  
 Activation via radio or automatically through first 10 pulses.

### Data

- Meter ID
- Meter Reading
- Alarms (leak, cable cut\*, reverse flow\*, broken pipe, internal errors, low battery)
- Fixed Date Reading
- Data Logger

\* Depending on the connected pulse device

### Assembly versions

For Sensus mechanical water meters prepared for HRI or HRI-Mei pick-up an assembly with connected pulser exists.



qualityaustria  
 Succeed with Quality

Certified according to ISO 9001  
 Quality Management System Quality Austria Reg.no. 3496/0

### UK & Ireland Enquiries

Sensus UK Systems Ltd, 3 Lindenwood Crockford Lane, Chineham Business Park  
 Basingstoke RG24 8QY UK  
 T: +44 (0) 1256 372800 F: +44 (0) 1256 707203 Email: info.gb@xyleminc.com [www.sensus.com](http://www.sensus.com)

### International Enquiries

Sensus GmbH Hannover, Meineckestraße 10, D-30880 Laatzen Germany  
 T: +49 (0) 5102 74-0 F: +49 (0) 5102 74-3341 Email: info.int@xyleminc.com [www.sensus.com](http://www.sensus.com)