



Sector	Code
Irrigation	IR

Size	End Connection
DN25 ^{3/4"}	Female Threaded
DN25 1"	Female Threaded
DN40 1 1/2"	Female Threaded
DN50 2"	Female Threaded

Primary Feature	Code
Basic Valve	205
Solenoid Controlled Valve	210
Pressure Reducing Valve	220
Pressure Reducing & Sustaining Valve	223
Pressure Sustaining Valve	230
Quick Pressure Relief Valve	23Q
Level Control Valve	250

Other primary features available on request.

Additional Feature	Code
No Additional Features	00
Hydraulic Relay	50
N.C. With Hydraulic Relay	54
Solenoid Controller	55
Modulating Horizontal Float	60

Pattern	Code
Globe	G
Angle - Available for: 1 1/2" - 2"	A

Construction Materials	Code
Nylon Glass Filled (Standard)	P

End Connection	Code
BSP-T Female Threaded	BP

Voltage-Main Valve Position (When Solenoid De-Energized)	Code
24VAC - Normally Closed	4AC
24VAC - Normally Open	4AO
24VDC - Normally Closed	4DC
24VDC - Normally Open	4DO
12VDC - Latch Solenoid S-985 (3 Leads)	1DS
12VDC - Latch Solenoid S-982 (2 Leads)	2DS
9VDC - Latch Solenoid	9DS

Other electrical ratings available on request.

Additional Attributes - Unlimited Selection	Code
3-Way Control Loop	X
External Control Pressure	e
Flow Stem	M
Internal Feed	N
Orifice Assembly	U
Manual Selector	Z
Plastic Pressure Test Point	5
Pressure Gauge	6
Schrader Valve	SCH

Other additional attributes are optional.
Please consult with Deeco for more information.